



Durable  
Beautiful  
Elegant  
Dependable

## TRIO Ingenuity at Work

Designed for special applications where the projection of a regular lateral arm is limited by the available width, this Alutex exclusive retractable awning can extend beyond those limits by reaching up to 13' in projection in as little as 8' of width. This without compromising its elegant design.

Particularly useful in condominiums and narrow patio applications, Trio can be installed like any classical retractable lateral arm awning. No more need for eye soar overlapping arms. Its special design allows to virtually retracting its arms within the same space necessary in a regular lateral arm awning.

### Product Features

#### **Durable.**

Engineered to satisfy the most stringent mechanical requirements, Trio's arms are tested to last twice the expected life span commonly referred to by the industry and its stainless steel cables are protected with an UV resistant coating to increase their endurance.

#### **Beautiful.**

Trio's sleek design has been achieved to enhance the value of your home. With the extensive variety of colors offered today by hundreds of vivid fabrics, the finish of its parts, its compact look when totally retracted, and the flexuosity of its arms when fully extended, Trio has the look you want.

#### **Elegant.**

They say elegance is to stand inconspicuously. So, the discrete design of Trio is meant to blend with the siding of your house while extending your presence to your immediate outdoor lending graceful ambiance to any setting. You will appreciate Trio's generous size and uncommon strength.

#### **Dependable.**

Built only with the finest materials, Trio frames are finished with electrostatic powder coated epoxy paint on all its parts to assure the most durable and yet elegant finishing against chipping, cracking, and fading. Like all Alutex awnings, Trio is covered by a ten-year warranty.



# Product Highlights



When closed, it takes the same space of a regular lateral arm awning.



Front section opens first.



Front section fully extends.



Back section starts opening.



Back section fully extends.



Larger projection is reached also when width is limited.

## Technical Specifications

Width Range	8' to 14' (1/4" increment)
Projection Range	8'7", 10', 12', 13'
Side dimension w/Hood	10" H x 10" W
Side size w/out Hood	9" H x 9" W
Hood	Optional
Hood Shape	Round
Opening Control	Manual Gear or Motorized
Installation Option	Wall, Soffit, Roof Mounted
Bracket Size	8 1/2" H x 2 3/8" W x 4 3/4" L
Standard Pitch Control	Bolt Lock System

Crank Pitch Control	N/A
Drop Down Valance	N/A
Fabric Options	Over 300 acrylic patterns
Leg Kit	Optional
Standard Frame Color	White



Custom Frame Color	Any RAL color (on request)
Frame Warranty	10 Years

CAUTIONARY AND IMPORTANT OPERATING INFORMATION: Retractable Awnings contain strong springs under tension. Retractable awnings are specifically designed to be retracted under inclement weather conditions and be used primarily for sun protection. They are not designed to withstand high winds, heavy rain or snow. During those times, awnings must be fully retracted to prevent damages not covered by warranty.